

AN AFFORDABLE ADVANCED SPACE VLBI MISSION

J. S. Ulvestad, D. L. Meier, D. W. Murphy, R. A. Preston, J. G. Smith

Jet Propulsion Laboratory, California Institute of Technology, Pasadena, California) USA

We have defined an affordable Advanced Space VLBI mission that would be a successor to the VSOP and Radioastron missions that will take place in the mid-1990s. The major focus of this mission would be to improve the sensitivity over VSOP by a factor of 30-100 at frequencies between 1.6 and 22 GHz, with reasonable performance also available at 43 GHz. Design goals for the 1.6- to 22-GHz range are (1) a 30-111 space antenna with 60% aperture efficiency; (2) a data rate of at least 1 Gbit/s; and (3) a system temperature of 10 K. The space antenna would be an inflatable surface, perhaps with additional stiffening to provide the desired high-frequency performance. Its design would be strongly influenced by a NASA IN-STEP (In-Space Technology Experiments Program) experiment scheduled for 1995, in which a 14-m-diameter inflatable reflector structure will be deployed, with a goal of achieving an r.m.s. surface precision better than 1 mm. The technology for recording at least 1 Gbit/s already exists and will be built into the M1{ IV recording and correlation system now under development by the Haystack Observatory and the European VLBI Network. The low system temperatures desired will require continued development of long-lifetime, Space-qualified cooling systems.

Each of the three design goals listed above would provide a factor of 3-5 improvement over the interferometer sensitivity for VSOP. When **they** are combined, the 22-GHz interferometer sensitivity for the advanced mission would be about 60 times better than for VSOP. On a baseline to a VLBA antenna, the sensitivity would be about 10 times better than for two VLBA antennas recording 128 Mbit/s. The added sensitivity would enable new Space VLBI investigations including (1) high spatial- and time-resolution imaging of weak cores of active galactic nuclei (AGN) such as Seyfert galaxies; (2) much higher dynamic range maps of core-dominated AGN; (3) imaging of radio stars in their quiescent states; and (4) observations of a large enough sample of extragalactic H₂O masers to derive an improved value for Hubble's constant.